

## Alternate Operating Scenarios For NDCX-II\*

*Thursday, 16 August 2012 14:35 (2h 40m)*

W. M. Sharp, A. Friedman, D. P. Grote, R. H. Cohen, S. M. Lund  
Lawrence Livermore National Laboratory  
Livermore, California, 94550, USA

J.-L. Vay, W. L. Waldron, A. Yuen  
Lawrence Berkeley National Laboratory  
Berkeley, California, 94720, USA

NDCX-II is a newly completed accelerator facility at LBNL, built to study ion-heated warm dense matter and aspects of ion-driven targets for inertial-fusion energy. The baseline design calls for using twelve induction cells to accelerate 40 nC of Li<sup>+</sup> ions to 1.2 MeV. During commissioning, though, we plan to extend the source lifetime by extracting less total charge. For operational flexibility, the option of using a helium plasma source is also being investigated. Over time, we expect that NDCX-II will be upgraded to substantially higher energies, necessitating the use of heavier ions to keep a suitable deposition range in targets. Each of these options requires development of an alternate acceleration schedule and the associated transverse focusing. The schedules here are first worked out with a fast-running 1-D particle-in-cell code ASP, then 2-D and 3-D Warp simulations are used to verify the 1-D results and to design transverse focusing.

\*Work performed under the auspices of US Department of Energy by LLNL under Contract DE-AC52-07NA27344 and by LBNL under Contract DE-AC03-76SF00098.

**Primary author:** SHARP, W. M. (Lawrence Livermore National Laboratory)

**Presenter:** SHARP, W. M. (Lawrence Livermore National Laboratory)

**Session Classification:** Poster session